

BCL4S015UCL2

BayLan Media Converter 1000Base-TX to 1000Base-LX Singlemode 20KM



FEATURES

- One-channel Media conversion between 1000Base-TX and 1000Base-LX
- Fiber media allow: Single mode fiber using SC connector;
- Link Pass Through Function
- Auto negotiation of duplex mode on TX port
- Auto MDI/MDI-X for TX Port
- Full write-speed forwarding rate
- Front Panel status LEDs
- Used as a status-alone device or with a chassis
- Hot-Swappable when used with a chassis

SPECIFICATIONS

Applicable Stranded	IEEE 802.3ab 1000Base-TX IEEE 802.3z 1000Base-LX
Power Consumption	5.5 Watts (Maximum)
Speed	PWR, LINK/ACT
Media Interface	RJ-45, SC
Forwarding Rate	148, 8000pps for 1000Mbps
Duplex Mode	Full Duplex Mode
Cable	1000 Base-TX 4 Pair Cat. 5, EIA/TIA-568 100-ohm screen twisted-Pair(STP), up to 100m 1000 Base LX 9/125µm single-mode fiber optic cable up to 20 km
Weight	305 g
Power	External power Adaptor 7.5V 1.5A
Dimensions	L120 x W88 x H25 mm
Operating Temperature	-0°C~ 70°C
Storage Temperature	-10°C ~70°C
Humidity	10~90%, non-condensing
Emissions	FCC part 15 Class A, CE Mark

Specifications are subject to change without prior notice with advancement in technology.