

BOSC12448AH **BayLan Optical Splice Enclosure** **Inline/Duct Horizontal** **(2*In 2*Out)**



BayLan Horizontal Fiber Optic Splice Closure provides space and protection for the fiber Optic cable splicing and joint. They are perfect sealed design to be waterproof and dust proof. **BayLan** Horizontal Fiber Optic Splice Closure is good in performance and competitive prices.

Features:

- Horizontal Optical Splice Enclosure used for the protective connection between two or more optical cables
- The box adds ageing-resistant in imported high tensile construction plastic, out-faster is made up of stainless steel
- Overlap structure in splicing tray easy to install
- Suitable for Ordinary fiber and ribbon fiber optic cable
- Perfect leak proof
- Perfect and reliable sealing operations
- Full accessories included for convenient operations
- Fiber Optic Splice Closure can be used repeatedly
- For Aerial, underground, direct buried, wall mounting, hand hold and duct mounting application
- Total Capacity of Fiber 48cores , It can be extend up to 96fibers
- Fiber Optic Splice Tray 4 Pieces of 12/24C Fiber Optic Splice Tray

Specification:

- **Temperature** : -40 to +80°C
- **Atmosphere** : 70 to 106kpa
- **Sealing property at normal temperature**: Internal Pressure: 70KPa, without decrease in 72hours
- **High temperature sealing property** : Internal pressure:70KPa, without decrease in 168 hours at 60°
- **Insulated resistance** : >2x 104MΩ
- **Dimension** : LxWxH: 410x200mmX110mm
- **Additional Loss** : No additional loss when optic fibers are winded in the splice trays
- The ageing time of the material of the enclosure is beyond 20 years under normal conditions

Specifications are subject to change without prior notice with advancement in technology.