
POS80-Bluetooth Thermal Receipt Printer USB+Bluetooth Dia 80mm, 90mm/sec with Cutter

Compared to the traditional Thermal Receipt printer, Mini printer has smaller body, more reliable capability, more steady printing and portable advantages. The mini printer cable work on a lot of locations, such as TAXI bill printing, administrative fees receipt printing, post receipt printing, restaurant ordering information printing, online payment information printing, etc. With the rapid popularity of smart-mobile, tablet and so on, Mini printer will be more widely used in the near future.

Applications:

- The mobile police system
- The tobacco distribution system
- The utility meter reading system
- The mobile office / mobile logistics systems



Features :

- It applies mobile products to supporting the use, and suited to outdoor work environment.
- The feature has small size, lightweight, reliable performance, simple to connect,
- Easy to use.
- Support Windows, Java, Android, iPhone OS
- Bluetooth, USB and RS232
- High printing speed 90mm/sec.
- 100KM long printing life.
- The portable instrumentation
- The testing equipment, ancillary equipment
- Low operating costs (no ribbons, ink cartridges)

Specifications are subject to change without prior notice with advancement in technology.



The Brightest Choice of Networking & Communication

Print Method	Thermal Line Printing
Print Speed	Upto 90mm/sec.
Thermal film(Reliability)	100KM
Resolution	203dpi
Effective Paper Width	72mm (576dot)
Paper Dimensions	79±0.1mm x diameter 40.0mm
Paper Thickness	0.06 ~ 0.08mm
Power Supply (optional)	Rechargeable Lithium batteries
Battery Lithium	7.4V DC/2000mAH
Charging Mode	DC 9V / 1.5A (Support the battery display function)
Battery Duration	At least 120m continuous printing (under 25% printing density)
Battery Charging	Quick Charging : About 3 hours to reach full charge
Print Parameters	support to download the Logo trademark
Character Size	384 dots/line Font A: 12*24dots / 1.5x3.0mm (WxH) Font B: 9*17dots / 1.1x2.1mm (WxH) Simplified /Traditional : 24x24 /3.0x3.0mm (WxH)
Printing Chinese Characters	Chinese: simplified Chinese 24x24 point, support 18030 font library, Support Taiwan and HK traditional(complex font)
ANK	ANK characters
Extended Character Table	OEM437 / KATAKANA / OEM850 / OEM860 / OEM863 OEM865 / West Europe / Greek / Hebrew / East Europe / Iran / WPC1252 / OEM866 / OEM852 / OEM858 / IranII / Latvian / Arabic / PT151,1251 / OEM747 / WPC1257/ Vietnam / OEM864 / Hebrew / WPC1255 /Thai
Emulation	ESC/POS compatible command set
Interface	Standard RS232/USB, Bluetooth 2.0
Paper loading Method	Drop-in easy loading
Character Set	Alphanumeric / Chinese Kanji
NV bit Image/Logo	Download and printing supported
Data Buffer	Upto 10K bytes
Other Features	Paper detection, Power detection, Manual shut down
Color	Dark Grey
Environment	Operating : 0°C ~+ 50°C , 10%RH ~ 90% RH Storage : -20°C ~ +70°C , 5%RH ~ 95% RH
Dimensions	103.8(L) x 100(W) x 46(H)
Weight	190g

Specifications are subject to change without prior notice with advancement in technology.